ReVent FAB Analysis		
Feature	Advantage	Benefit
Shield	Designer Look Low Profile Cleaner Quieter	Modern design, fits any décor Shield blends into the ceiling and becomes less noticed Shield flows dust through the fan to the outside, does not collect Patented shield shape helps reflect sound back into the fan
SheetLock Installation	Attaches Directly to Sheetrock No Screws Needed Saves Installation Time Stronger	SheetLock tabs mount to 5/8 inch or 1/2 inch sheetrock No screws needed when mounting to sheetrock Save time mounting directly to the sheetrock, no wood mounting needed All sides grip the sheetrock and hold better and stronger then tradition brackets
Trim Ring	Improves Airflow Reduces Air Lose Hides Rough Cut	Directs the airflow into the fan and exhaust pipe Losing heated or cooled air through openings is reduced Provides a finished look
LED Lighting Selectable	Easy Selectable Three Level Settings 2700K, 4000K,5000K	Select lighting temperature with a simple slide switch on the fan shield Match the current lighting in any room
LED Lighting Dimmable	1,000 Lumens Dimmable	High lumens create bright light for bathroom tasks Dimming lets you create the perfect LED lighting brightness
Energy	Energy Star Cost	Your guarantee energy efficiency is certified All ReVent models are under \$8 per year to operate
Whole House Ventilation	ASHRAE, Title 24	Selected models meet ASHRAE code requirements Selected Intelligent Humidity Control models meet Title 24 and Cal Green
Intelligent Humidity	Intelligent Family and Tenant Friendly	ReVent knows the temp and humidity levels and learns the room, accurately turns the fan ON/OFF People turn OFF the fan after use, Intelligent Humidity runs the fan until the room is dry.